

NEW



LED 2835 | CRI >90 | 126 lm/W | 48 Vdc


Strisce flessibili a LED 48V autoadesive IP65

- > LED 2835 ad alta efficienza e a bassa caduta di tensione
- > Protezione in silicone morbido contro la polvere e i getti d'acqua
- > Realizzata in moduli da 7 LED per una diminuzione delle perdite in calore e migliore resa luminosa, basso consumo, alto rendimento
- > Disponibile nei colori standard 3000°K e 4000°K
- > Fornite in nastro di 20m e cavetto di collegamento 200mm
- > Alimentazione da un solo lato


48V Flexible adhesive LED strips IP65

- > LED 2835 with high lumen efficiency and low voltage drop
- > External soft silicon protection against dust and water jets
- > 7 LED segments for a reduction of warm losses and higher lumen efficiency, low consumption, higher efficiency
- > Color temperatures available: 3000°K e 4000°K
- > Supplied in 20m roll with connection cable 200mm
- > Powered by one side only

Codice Code	Colore luce Light color (°K)	Alimentazione Power supply (Vdc)	Watt/metro Watt/meter (W/m)	Potenza totale Total power (W)	LED/metro LED/meter	Lumen/metro Lumen/meter (lm/m)	Lumen/Watt (lm/W)	CRI	Unità di taglio Cutting unit (mm)	IP
A41H48140A30	3000	48	14.4	288	140	1800	125	>90	50	65
A41H48140A40	4000					1825	126			



Alimentatori LED associabili
Attachable LED power supplies



IP 20

Vedi la serie completa sul nostro Catalogo Lighting
See the complete series in our Lighting Catalog

ON-OFF

Serie
Series
STANDARD

LE7548
LE10048
LE15048
LE20048
LE32048

DIMMERABILI/DIMMABLE

DIM
PUSH230Vac
DALI | 0/1-10V

LE2548DP
LE7548DP
LE10048DP
LE15048DP

